



ANDROID STB BOX Model DV6801-S2

Features	Category	Dual core, ANDROID DVB Box, OTT BoX, Android media player
	Digit Video Broadcast	Fully compliant with HD DVB-S2, 7 days EPG,USB PVR, Timeshift, Program playback, Timing playing
	Local Media Playback	Video/Audio/Picture
	Network Streaming	HMTL5 ,RTSP,HLS,Smooth streaming
	External storage	USB storage, SD card max to 32GB
	Games	Android 2D/3D games
	System Upgrading	Via u-disk or SD card
	Mobilephone Control	Can using the android and iOS mobilephone to control
	Multi-screen interactive	DLNA,Airplay,TVCast,Miracast.
	DRM	Verimatrix and Playready. (Optional)
	Rich Android application	Facebook, YouTube, Skype, etc.(Optional)
Core System	SoC	Amlogic 8726-MX
	CPU	ARM Dual Cortex-A9 1.5GHz
	GPU	Mali-400 MP
	DRAM	DDRIII 1GB
	Flash	MLC 4GB
	Android OS	Android4.2
Video	Decoder	MPEG-1/2/4 ASP, DivX 3/4/5, XviD, H.264(1920x1080p @ 30fps), SVC, MVC,VC-1, WMV, H.263, AVS, WebM, RMVB, RealVideo, VP6, VP8 up to 1080P
	Format	*.mkv, *.ts, *.m2ts, *.tp, *.mov, *.mp4, *.rm, *.rmvb, *.wmv, *.avi, *.mpg, *.mpeg, *.dat, *.vob, *.flv, *.asf
	Resolution	720P, 1080I, 1080P, 4:3 and 16:9 video ratio
Audio	Decoder	MPEG 1/2/2.5, Audio Layer 1/2/3, WMA Version 4, 4.1, 7, 8, 9, WMA Pro, PCM, Vorbis, Flac, ALAC, APE, AAC-LC, AAC-HE, AC-3, DTS, Real Audio
	Format	*.mp3, *.wma, *.wav, *.ogg, *.flac, *.mka, *.mp4, *.aac, *.ape, *.alac, *.mpeg, *.mp1, *.mp2, *.mpa, *.ogg
Subtitle	Formats	SMI, SRT, SSA, ASS,SUB, SUB+IDX, ISO Navigation
Picture	Formats	jpeg, bmp, png
Network	Ethernet Port	RJ45 Interface 10M/100M adaptive
	Wi-Fi	Build in Wi-Fi 802.11b/g/n, Wi-Fi Hotspot,Wi-Fi Slave mode
	Features	Fully compliant with HD DVB-S2 Standard
	Tuner Type	SHARP7306+AVLINK6211

Tuner Paramete	Frequency Range	950~2150MHZ
	Input Level	level:-65~-25dBm
	Imput impedance	75Ω
Connectivity	HDMI	HDMI1.4
	SD card slot	SD card slot
	Ethernet	RJ45
	A/V	1 to 3 RCA 3.5mm round interface
	Digit Audio	S/P DIF Optical output
	USB Host	2 Standard USB port 2.0
	IR	IR
	Antenna input	Antenna input and RF-OUT F-connector
	Power	DC IN 12V/1.2A 3.5*1.5*8mm round interface
Dimensions	Product	165mm*145mm*38mm
	Remote	175mm*45.2mm*29mm
Proposed Accessory	Remote control, Power Adapter, 1 to 3 RCA Cable, 1M HDMI Cable	
Picture	Front panel	
	Rear panel	
	Remote control	